



Surface Mount
Pair of ball-joint wall
mounts included



Plasma Screen Mount
Mounting brackets that fit most
popular flat panel displays

AUDIO... ANYWHERE...

Powered Audio Solutions from ALTEC LANSING®



SLS5220 POWERED AUDIO 2.0 SPEAKER SYSTEM

Plug & Play audio from the world's leader in Powered Audio speaker systems. Altec Lansing's SLS5220 delivers full-range audio using an LF enhancement circuit that adds one octave of low frequency performance without damaging vocal or speech intelligibility. Use the SLS5220 in corporate meeting facilities, clubs, restaurants & retail stores. Just take the audio output from your projector, CRT, plasma screen or music source directly into the dual RCA inputs on the master speaker. Your ears simply won't believe the full range sound from this compact speaker system. Your client won't believe how much money you saved them by eliminating the power amplifier from the budget.

HIGH FIDELITY AUDIO...ANYWHERE
...from Altec Lansing

**ALTEC
LANSING®**

PROFESSIONAL

A DIVISION OF ALTEC LANSING TECHNOLOGIES, INC.

www.altecpro.com



SLS5220 2.0 POWERED AUDIO SPEAKER SYSTEM

SPECIFICATIONS

FREQUENCY RESPONSE 70 HZ – 20 KHZ (- 10 DB)

MAXIMUM OUTPUT 99 DB SPL @ 1M

POWER HANDLING

SYSTEM: 24W RMS
EACH SATELLITE: 12W RMS @ 1% THD (BOTH CHANNELS DRIVEN)

SYSTEM THD < 0.6% THD @ 1 KHZ (INPUT TO AMP OUTPUT)

SIGNAL-TO-NOISE RATIO < 75 DB (A WEIGHTING)

INPUT IMPEDANCE > 10 K OHMS

INPUT SENSITIVITY 0 DBU (.775 VRMS)

MAXIMUM INPUT LEVEL +17 DBU (5.5 VRMS)

VOLUME CONTROL 90 DB ATTENUATION MAXIMUM

TREBLE LEVEL CONTROL +/- 9 DB @ 10 KHZ

BASS LEVEL CONTROL +6 TO -10 DB @ 100 HZ

COMPONENTS ONE 1" HORN LOADED TWEETER
ONE 3" MID-BASS DRIVER MAGNETICALLY SHIELDED

AC POWER REQUIREMENTS 100V – 240V @ 50 HZ TO 60 HZ (WORLDWIDE)

CABLES STEREO RCA MALE TO STEREO RCA MALE (16.4' / 5M)
STEREO RCA MALE RIGHT ANGLE TO TINNED WIRE (16.4' / 5M)

INPUT CONNECTIONS DUAL RCA ON MASTER SPEAKER

MOUNTING OPTIONS BALL JOINT WALL MOUNTS (PAIR)
DISPLAY MOUNTING BRACKETS (PAIR)

ENCLOSURE MATERIAL & FINISH BLACK INJECTION-MOLDED PLASTIC WITH METAL MESH GRILLE

DIMENSIONS 5.2" (W) X 2.5" (D) X 10.2" (H)
132MM (W) X 63MM (D) X 260MM (H)

WEIGHT

MASTER SPEAKER: 2 LBS. / 0.91 KG
SATELLITE SPEAKER: 1 LB. / 0.45 KG
SHIPPING WEIGHT: 7 LBS. / 3.17 KG

**ALTEC
LANSING®**

PROFESSIONAL

Altec Lansing Professional, A Division of Altec Lansing Technologies, Inc. / www.altecpro.com
Tel. 405-848-3108 / Fax. 405-848-3217 / proinfo@alteclansing.com / Oklahoma City, OK USA